

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : Water Repellent Coating for Glass and Perspex
UFI : S2T2-30KE-T00R-5JSX
Product code : G5
Type of product : Sealant

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Intended for general public
Main use category : Consumer use
Use of the substance/mixture : Automotive Coating

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

GTECHNIQ LTD Bridge Business Park Upper Heyford NN7 3FA Northampton - United Kingdom T +44 (0)1604 962 553 uk@gtechniq.com - www.gtechniq.com	GTECHNIQ POLAND Detailing Services Pory 60/42, 02-757 Warsaw T +48 500 800 639
---	--

1.4. Emergency telephone number

Emergency number : +44 (0)1933 445 260
For Chemical Emergency Call 24hr / day, 7 days / week.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Warning
Hazard statements (CLP) : H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H412 - Harmful to aquatic life with long lasting effects.

Water Repellent Coating for Glass and Perspex

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 - Wear eye protection, protective clothing, protective gloves. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	(CAS-No.) 93685-81-5 (EC-No.) 297-629-8 (REACH-no) 01-2120752626-49-XXXX	12.5 - 20	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413
sulphuric acid ... % (Note B)	(CAS-No.) 7664-93-9 (EC-No.) 231-639-5 (EC Index-No.) 016-020-00-8 (REACH-no) 01-2119458838-20-XXXX	5 - 10	Met. Corr. 1, H290 Skin Corr. 1A, H314
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	(EC-No.) 923-037-2 (REACH-no) 01-2119471991-29-XXXX	5 - 10	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Specific concentration limits:

Name	Product identifier	Specific concentration limits
sulphuric acid ... %	(CAS-No.) 7664-93-9 (EC-No.) 231-639-5 (EC Index-No.) 016-020-00-8 (REACH-no) 01-2119458838-20-XXXX	(5 ≤C < 15) Eye Irrit. 2, H319 (5 ≤C < 15) Skin Irrit. 2, H315 (15 ≤C < 100) Skin Corr. 1A, H314

Note B : Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label.

Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Full text of H-statements: see section 16

Water Repellent Coating for Glass and Perspex

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately. Get medical advice/attention if you feel unwell. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes skin and eye irritation.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a doctor.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Explosion risk in case of fire.
Reactivity in case of fire	: Not known.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide. hydrocarbons.

5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Do not attempt to take action without suitable protective equipment.
6.1.1. For non-emergency personnel	
Protective equipment	: Wear suitable protective clothing, gloves and eye or face protection. In case of insufficient ventilation, wear suitable respiratory equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing fume, mist, spray, vapours.

Water Repellent Coating for Glass and Perspex

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb spillage.
- Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).
- Other information : This material and its container must be disposed of as hazardous waste.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing fume, vapours, mist, spray. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a dry place. Store in a closed container. Store locked up. Keep cool.
- Incompatible materials : Strong acids. Strong bases. Strong oxidizing agents.
- Heat and ignition sources : No flames, no sparks. Eliminate all sources of ignition.
- Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

sulphuric acid ... % (7664-93-9)

United Kingdom - Occupational Exposure Limits

Local name	Sulphuric acid
WEL TWA (mg/m ³)	0.05 mg/m ³ mist
Remark (WEL)	The mist is defined as the thoracic fraction
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Avoid all unnecessary exposure. PPE compliant to the recommended EN/ISO or equivalent standards should be selected.

Water Repellent Coating for Glass and Perspex

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Materials for protective clothing:

Wear suitable coveralls to prevent exposure to the skin

Hand protection:

Protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask. Where exposure through inhalation may occur from handling or use, respiratory protection equipment is required. Exposure limits for airborne contaminants must not be exceeded.

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Odour	: Solvent-like.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 100 °C
Flash point	: 31 °C
Auto-ignition temperature	: 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 0.14 mbar
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.92 g/cm ³
Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 310.978 mm ² /s
Viscosity, dynamic	: 286.1 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0.6 vol %
Upper explosive limit (UEL)	: 7 vol %

9.2. Other information

VOC content : ≤ 5 %

Water Repellent Coating for Glass and Perspex

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

sulphuric acid ... % (7664-93-9)	
LD50 oral rat	2140 mg/kg bodyweight Animal: rat, 95% CL: 1540 - 2990
LD50 oral	2140 mg/kg bodyweight
LC50 inhalation rat (mg/l)	0.375 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 inhalation rat (Dust/Mist - mg/l/4h)	375 mg/l

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Water Repellent Coating for Glass and Perspex

Viscosity, kinematic	310.978 mm ² /s
----------------------	----------------------------

Water Repellent Coating for Glass and Perspex

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 12: Ecological information

12.1. Toxicity

- Ecology - general : Harmful to aquatic life with long lasting effects. Before neutralisation, the product may represent a danger to aquatic organisms.
- Hazardous to the aquatic environment, short-term (acute) : Not classified
- Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

sulphuric acid ... % (7664-93-9)	
LC50 fish 1	> 16 mg/l
EC50 Daphnia 1	> 100 mg/l Test organisms (species): Daphnia magna
EC50 other aquatic organisms 1	> 100 mg/l waterflea
EC50 other aquatic organisms 2	> 100 mg/l
EC50 72h algae (1)	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	0.15 mg/l Test organisms (species): other:Tanytarsus dissimilis
NOEC chronic fish	0.31 mg/l Test organisms (species): Salvelinus fontinalis

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

sulphuric acid ... % (7664-93-9)	
Partition coefficient n-octanol/water (Log Pow)	-2.2

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Regional legislation (waste) : Disposal must be done according to official regulations.
- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- Additional information : Handle empty containers with care because residual vapours are flammable.
- Ecology - waste materials : Avoid release to the environment.






SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

Water Repellent Coating for Glass and Perspex

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1993	UN 1993	UN 1993	UN 1993	UN 1993
14.2. UN proper shipping name				
FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated)	Flammable liquid, n.o.s. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated)
Transport document description (ADR)				
UN 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated), 3, III, (D/E)	UN 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated), 3, III	UN 1993 Flammable liquid, n.o.s. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated), 3, III	UN 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated), 3, III	UN 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated), 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Water Repellent Coating for Glass and Perspex

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport by sea

Special provisions (IMDG)	: 223, 274, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 274, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 274, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Water Repellent Coating for Glass and Perspex

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

VOC content : ≤ 5 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.