

HALOv2 – Application Information

Storage and use:

- Shake bottle well and wear gloves
- To apply HALO, your vehicle must be indoors and remain indoors, for at least 12 hours after the coating has been applied. For best results, good lighting is essential
- If applying to previously installed film, wash and decontaminate the vehicle with Gtechniq W5 Citrus All Purpose Cleaner and W6 Iron and General Fallout Remover
- Spray a 30% dilution of isopropyl alcohol (IPA) onto a Gtechniq MF1 Microfibre Cloth
- With your surface fully cooled, buff to remove any fingerprints or other surface contaminants. This process ensures you to get the maximum number of chemical bonds between HALO and the PPF or Vinyl Wrap
- Apply HALO evenly on the application pad and set the bottle aside
- Apply using the AP2 applicator provided in overlapping strokes to an area roughly 2 foot by 2 foot (60cm by 60cm), or work to the bodylines of the vehicle
- After coating a panel remove residue with a Gtechniq MF1 Microfibre Cloth Always remove from further than you have applied, working from the outside in
- Once applied carry out a final check using a bright, diffused light source – this will ensure no excess residue remains on the surface
- An unopened bottle of HALO has a 12-month shelf life from the time of purchase
- Always store in a cool/dry place, out of direct sunlight
- Use within 3 months of opening and ensure original cap is fitted.
- **Note... HALOv2 is a single layer coating**
- Refer to the Gtechniq Australia YouTube channel for all of our how to apply videos:-

Scan here:-

