

Gtechniq Marine Ceramic Top - Application Information

Storage and Use

- To apply Marine Ceramic Top make sure your vessel is indoors and can stay indoors for 12 hours after application, do not apply in direct sunlight
- Note Marine Ceramic Top is a single layer application
- For best results only apply the product at a temperature between 5°C and 25°C
- Shake well and wear gloves
- If using as a stand alone coating, wash and decontaminate your gelcoat/paintwork thoroughly prior to application. If required, polish your gelcoat/paintwork, either by machine or hand, to remove any imperfections
- Spray Marine Panel Wipe onto a Gtechniq MF1 Microfibre Cloth and wipe down each panel in small sections
- Soak the application pad with Marine Ceramic Top and work the liquid into the pad to get an even saturation
- Replace the lid on the bottle and set aside - do not keep the bottle in your hand as this promotes premature curing
- Apply in overlapping strokes to an area roughly 2ft by 2ft (60cm by 60cm), or work to the bodylines of the vessel
- After approximately 1 to 2 minutes remove the residue with a Gtechniq MF1 Cloth - you may need to buff the same area several times, however, avoid doing it with too much force. We recommend the use of 2 cloths at any one time. Make sure the cloths are rotated during residue removal to prevent Marine Ceramic Top curing in the cloth - this can make buffing residue difficult
- Inspect the surface for excess residue with a bright, diffused light source
- If you do not remove all the excess residue and it cures fully then you should polish the area and reapply Marine Ceramic Top
- As soon as you finish, put your MF1 cloths in water, wash and dry them as soon as possible - never re-use an already used MF1 cloth for ceramic coatings
- If you are overcoating Marine Ceramic Base with Marine Ceramic Top wait a minimum of 4 hours after you have applied the Marine Ceramic Base to apply Marine Ceramic Top, or Marine Fast Coat
- Store Marine Ceramic Top in a cool, dry place
- Use within 3 months of opening
- **Do not apply Marine Ceramic Top directly to rubber, hard plastics or lights**
- Refer to the Gtechniq Australia YouTube channel for all of our how to apply videos