

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : Hydro Coat
Product code : C3

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Intended for general public
Main use category : Consumer use
Use of the substance/mixture : Automotive Care Products.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

GTECHNIQ LTD	Gtechniq France
Bridge Business Park Upper Heyford	455 Promenade des
NN7 3FA Northampton	Anglais
United Kingdom	06200 France
T +44 (0)1604 962 553	
uk@gtechniq.com - www.gtechniq.com	

1.4. Emergency telephone number

Emergency number : +44 (0)1933 445 260
For Chemical Emergency Call 24hr / day, 7 days / week.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to GB CLP (SI 2019:720 as amended)**

Serious eye damage/eye irritation, Category 2 H319
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to GB CLP (SI 2019:720 as amended)**

Hazard pictograms (GB CLP) :



GHS07

Signal word (GB CLP) : Warning
Hazard statements (GB CLP) : H319 - Causes serious eye irritation.
Precautionary statements (GB CLP) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P264 - Wash hands thoroughly after handling.
P280 - Wear eye protection, protective gloves.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical attention.

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with UK REACH Annex XIII

Component	
octamethylcyclotetrasiloxane; [D4] (556-67-2)	This substance meets the PBT criteria of UK REACH regulation, Annex XIII This substance meets the vPvB criteria of UK REACH regulation, Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP at a concentration equal to or greater than 0,1 %

Component	
octamethylcyclotetrasiloxane; [D4](556-67-2)	The substance is not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Labelling according to GB CLP (SI 2019:720 as amended)
Siloxanes and silicones, 3-[(2-aminoethyl)amino]propylme, di-me, hydroxyterminated	CAS-No.: 75718-16-0 EC-No.: 616-256-7	1.5 – 3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412
2-(2-butoxyethoxy)ethanol	CAS-No.: 112-34-5 EC-No.: 203-961-6 UK Index-No.: 603-096-00-8	0.14 – 1.4	Eye Irrit. 2, H319 STOT RE 2, H373
3-butoxypropan-2-ol; propylene glycol monobutyl ether	CAS-No.: 5131-66-8 EC-No.: 225-878-4 UK Index-No.: 603-052-00-8	0.14 – 1.4	Skin Irrit. 2, H315 Eye Irrit. 2, H319
propan-2-ol; isopropyl alcohol; isopropanol	CAS-No.: 67-63-0 EC-No.: 200-661-7 UK Index-No.: 603-117-00-0	0.5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
ethanol; ethyl alcohol	CAS-No.: 64-17-5 EC-No.: 200-578-6 UK Index-No.: 603-002-00-5	0.01 – 0.1	Flam. Liq. 2, H225
octamethylcyclotetrasiloxane; [D4] substance listed as UK REACH candidate (Octamethylcyclotetrasiloxane)	CAS-No.: 556-67-2 EC-No.: 209-136-7 UK Index-No.: 014-018-00-1	0.0035 – 0.014	Flam. Liq. 3, H226 Repr. 2, H361f Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: If experiencing respiratory symptoms: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: If skin irritation or rash occurs: Gently wash with plenty of soap and water.

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause slight irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Ingestion may cause nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: The product is not flammable.
Explosion hazard	: Product is not explosive.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Avoid fire-fighting water entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate area. Stop leak if safe to do so. Mark out the danger area with appropriate signs.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so. Mark out the contaminated area with signs and prevent access to unauthorized personnel. Ventilate area. Clean up any spills as soon as possible, using an absorbent material to collect it.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
-------------------------	---

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Always wash hands after handling the product.
Hygiene measures : Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

2-(2-butoxyethoxy)ethanol (112-34-5)

United Kingdom - Occupational Exposure Limits

Local name	2-(2-Butoxyethoxy)ethanol
WEL TWA (OEL TWA)	67.5 mg/m ³
	10 ppm
WEL STEL (OEL STEL)	101.2 mg/m ³
	15 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

ethanol; ethyl alcohol (64-17-5)

United Kingdom - Occupational Exposure Limits

Local name	Ethanol
WEL TWA (OEL TWA)	1920 mg/m ³
	1000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

United Kingdom - Occupational Exposure Limits

Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m ³
	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment - Report preview:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection - Report preview:

Chemical goggles or safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses, Safety goggles	Droplet, mist	Clear, With side shields	EN 166

8.2.2.2. Skin protection

Hand protection - Report preview:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves	Nitrile rubber (NBR)	4 (> 120 minutes)	0.5	2 (< 1.5)	EN ISO 374

8.2.2.3. Respiratory protection

No additional information available

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable.

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Explosive limits	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

2-(2-butoxyethoxy)ethanol (112-34-5)

Boiling point	225 °C
Flash point	78 °C
Auto-ignition temperature	78 °C
Vapour pressure	2.7 Pa 25°C

3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)

Boiling point	171 °C Atm. press.: 1013 hPa Decomposition: 'no'
Vapour pressure	1.05 mm Hg Temp.: 25 °C

octamethylcyclotetrasiloxane; [D4] (556-67-2)

Boiling point	175 °C Atm. press.: 1013 hPa Decomposition: 'no'
Vapour pressure	132 Pa Temp.: 25 °C

ethanol; ethyl alcohol (64-17-5)

Boiling point	78.3 °C
Flash point	13 °C Atm. press.: 1 atm
Auto-ignition temperature	12 °C
Vapour pressure	5730 Pa 25°C

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

Boiling point	82 °C
Auto-ignition temperature	12 °C
Vapour pressure	4400 Pa 25°C

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

None.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

2-(2-butoxyethoxy)ethanol (112-34-5)	
LD50 oral rat	4500 mg/kg
LD50 oral	6050 mg/kg mouse
LD50 dermal rabbit	2764 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), 95% CL: 2090 - 3645
LD50 dermal	2764 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 196 mg/l
ATE GB CLP (oral)	4500 mg/kg bodyweight
ATE GB CLP (dermal)	2764 mg/kg bodyweight
3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
LD50 oral rat	2700 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
ATE GB CLP (oral)	2700 mg/kg bodyweight
octamethylcyclotetrasiloxane; [D4] (556-67-2)	
LD50 oral rat	> 4800 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:
LC50 Inhalation - Rat	36 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

ethanol; ethyl alcohol (64-17-5)	
LD50 oral rat	15010 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 14450 - 15560
LD50 oral	10470 mg/kg bodyweight
LD50 dermal	15800 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 99999 mg/l
ATE GB CLP (oral)	10470 mg/kg bodyweight
ATE GB CLP (dermal)	15800 mg/kg bodyweight
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LD50 oral	4396 mg/kg bodyweight
LD50 dermal	12800 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	46600 mg/l
ATE GB CLP (oral)	4396 mg/kg bodyweight
ATE GB CLP (dermal)	12800 mg/kg bodyweight
ATE GB CLP (dust, mist)	46600 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
ethanol; ethyl alcohol (64-17-5)	
IARC group	1 - Carcinogenic to humans
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
2-(2-butoxyethoxy)ethanol (112-34-5)	
NOAEL (animal/male, F0/P)	> 452 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:
NOAEL (animal/female, F0/P)	> 470 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
STOT-single exposure	: Not classified
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
2-(2-butoxyethoxy)ethanol (112-34-5)	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	< 200 mg/kg bodyweight Animal: rat, Guideline: other:, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	350 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	880 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

ethanol; ethyl alcohol (64-17-5)	
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified

2-(2-butoxyethoxy)ethanol (112-34-5)	
Viscosity, kinematic	≈ 6.794 mm²/s
octamethylcyclotetrasiloxane; [D4] (556-67-2)	
Viscosity, kinematic	1.6 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

2-(2-butoxyethoxy)ethanol (112-34-5)	
LC50 - Fish [1]	1300 mg/l
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 1000 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 100 mg/l
EC50 96h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
LC50 - Fish [1]	560 – 1000 mg/l Test organisms (species): Poecilia reticulata
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

octamethylcyclotetrasiloxane; [D4] (556-67-2)	
LC50 - Fish [1]	> 22 µg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 15 µg/l Test organisms (species): Daphnia magna
ethanol; ethyl alcohol (64-17-5)	
LC50 - Fish [1]	14200 mg/l
EC50 - Other aquatic organisms [1]	5012 mg/l waterflea
EC50 - Other aquatic organisms [2]	275 mg/l
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
EC50 - Other aquatic organisms [1]	13299 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 1000 mg/l
12.2. Persistence and degradability	
Hydro Coat	
Persistence and degradability	Not established.
Siloxanes and silicones, 3-[(2-aminoethyl)amino]propylme, di-me, hydroxyterminated (75718-16-0)	
Persistence and degradability	Rapidly degradable
2-(2-butoxyethoxy)ethanol (112-34-5)	
Persistence and degradability	Rapidly degradable
3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
Persistence and degradability	Rapidly degradable
octamethylcyclotetrasiloxane; [D4] (556-67-2)	
Persistence and degradability	Rapidly degradable
ethanol; ethyl alcohol (64-17-5)	
Persistence and degradability	Rapidly degradable
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
Hydro Coat	
Bioaccumulative potential	Not established.
2-(2-butoxyethoxy)ethanol (112-34-5)	
Partition coefficient n-octanol/water (Log Pow)	0.56
ethanol; ethyl alcohol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.32

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component	
octamethylcyclotetrasiloxane; [D4] (556-67-2)	This substance meets the PBT criteria of UK REACH regulation, Annex XIII This substance meets the vPvB criteria of UK REACH regulation, Annex XIII

12.6. Other adverse effects

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecological information : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Transport document description				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport
Not applicable

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. United Kingdom

UK REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

UK REACH Candidate List (SVHC)

Contains substance(s) listed on the UK REACH Candidate List in concentrations $\geq 0.1\%$ or SCL: Octamethylcyclotetrasiloxane (EC 209-136-7, CAS 556-67-2)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Hydro Coat

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), UK

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.